

32" LCD Security Monitor

Model No. ; 32RTC



www.orionimages.com



■ World Leading Active Matrix TFT-LCD Panel

Truly flat LCD screen delivers razor sharp images

■ Hi Performance Image Processing Circuit

3D comb filter and deinterlace function realize perfect images

■ Real Industrial Mechanical Design

Rigid case comes with Heavy duty metal vessel, LCD protection glass

■ Versatile terminals for Security and Industrial Solution

Multiple input and output of Video(BNC Type), Audio, S-Video and RGB

Video

Screen Size	32"
Resolution	1366 x 768@60Hz
Contrast Ratio	1,000:1
Brightness	500cd/m2
Aspect Ratio	16:9
Color Depth	16.7M
Viewing Angle(H/V)	170°/170°
Pixel Pitch	0.51mm
Response Time	18ms
Scanning Frequency(Horizontal)	44 ~ 53KHz
(Vertical)	44 ~ 66Hz
Video System	NTSC

Audio

Built-in Speakers	Yes
Gradual Volume Increase	Yes

Terminals

RGB In (15-pin)	1
Video In(BNC Jack)	2
Video Out(BNC Jack)	2
Audio In	2
Audio Out	2
S-Video In	1
S-Video Out	1
Component In	1
DVI In	1
PC stereo In	1

Remote Control

Transmitter	Yes
-------------	-----

Special Features

2D comb Filter	Yes
Deinterlace Function	Yes
USB Hub	Not Available
DC 12V Power Outlet	Not Available
LCD Protection Glass	Yes
Rack Mountable Kit	Optional
Camera Mounting Hole	Yes
Multi-lingual Menu	English, Spanish, French, German, Italian
VESA™ Standard Compatible	Yes

Additional Information

Cabinet Dimensions	
W x H x D	30.7"x21.7"x3.9"/780x550x100
Weight	50.2lbs/22.6kg
Dimensions with Packaging	
W x H x D	30.9"x20.4"x7.2"/784x518x182
Weight	54.7lbs/24.6kg
Power Consumption	50W
Power Source	AC110~230V(50/60Hz)

Cabinet

Finish	Black
Tilt Stand	Yes

Warranty

Warranty: Parts/Labor	1 Year/1 Year
MTBF (Approx.)	30K hrs.

Regulations

TUV-NRTL(same as UL), CB, FCC(B), CE-EMC(LVD)

* Specification and Design are subject to change without prior notice.