



ELECTRONIC GROUP, INC
 480-635-8400 p * aegis-g2@aegiselect.com
 http://www.aegis-elec.com



VMTR-10.4V

10.4" Industrial Touch Screen Monitor

- 10.4" 5-Wire Resistive Touch Screen
- Resolution: 800 x 600 (SVGA)
- LED Backlights
- **TRU-Tuff** Ensures Maximum Shock/Vibration Resistance
- Can Be Customized To Meet Your Needs
- 3 Year Warranty

The VMTR-10.4V Touch Screen monitor utilizes 5-wire resistive touch technology; the screen can be activated via a finger, gloved hand, credit card or stylus. State-of-the-art LED backlights produce images that are exceptionally clear and bright; the touch contact activation points are extremely accurate. An extensive list of OEM options enables you to customize the VMTR-10.4V to meet your exact needs.


The VMTR-10.4V Touch Screen LCD monitor is built with industrial-grade components, and receives our exclusive **TRU-Tuff** treatment. The **TRU-Tuff** process includes: RTV silicone on all connections and critical components; all wires are dressed, tie-wrapped and secured; and ThreadLock on all screws. This, plus the rugged powder-coated steel enclosure, ensures maximum shock and vibration resistance. This monitor is ideal for a wide range of demanding applications including industrial, military, law enforcement, aviation, marine, inspection, surveying, cranes, oceanic, entertainment and transportation. **TRU-Vu** monitors are backed by our full 3-Year Warranty.

Specifications	
MODEL	VMTR-10.4V
LCD Panel	10.4" Color LCD; LED Backlights
Touch Screen Type	5-Wire Resistive Touch
Controller	USB
Resolution	800 x 600 (SVGA)
Display Area	8.31" (W) x 6.24" (H) (211.2 x 158.4 mm)
Pixel Pitch	0.264 mm
Display Colors	16:2 M
Aspect Ratio	4:3
Brightness	400 nits
Contrast Ratio	700:1
Viewing Angle	160° (H) x 130° (V)
Response Time	30 msec
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons
Video Inputs	VGA
Power Requirement	12 VDC (2.1 mm Barrel Plug); 90-240 VAC via Included Power Adapter
Power Consumption	10.4W (866 mA @ 12 VDC)
Enclosure	Powder-Coated Steel
Mounting	75 x 75 mm Rear VESA Mount Holes
Operating Temperature	-22° to +140° F (-30 to +60° C)
Humidity	5 - 90 % RH
Shock	50G, 20ms, Half-sine wave
Vibration	1.5G (10-200 Hz, P-P) 30 mins./axis (X,Y,Z)
Dimensions	10.13" (W) x 7.96" (H) x 1.73" (D) (257.4 x 202.2 x 44 mm)
Weight	3.90 lbs. / 1.77 kg

VMTR-10.4V

10.4" Touch Screen LCD Monitor

Dimensions:



Standard Accessories:

- 90-240 VAC Power Adapter
- VGA Cable
- USB Cable

Available Options:

- Move OSD Control Buttons onto Front Bezel
- Surface Capacitive Touch Screen
- DVI Video Input
- 11-36 VDC Operation
- Panel Mount
- Rack Mount
- Open-Frame Configuration
- Private Label
- Wall Mount or Tabletop Bracket
- Other Customer - Specific Modifications