



**ELECTRONIC GROUP, INC**  
 480-635-8400 p \* aegis-g2@aegiselect.com  
 http://www.aegis-elec.com

## SRMTR-21.5R

### 21.5" Sunlight Readable Touch Screen Monitor



- True Sunlight-Readable HD Monitor
- 1,000 Nits Brightness
- 5-Wire Resistive Touch
- Full HD Resolution: 1920 x 1080 (1080p/60)
- Widest Viewing Angle: 178° x 178°
- Anti-Reflective Coating
- Video Inputs: VGA, HDMI, DisplayPort, DVI
- Lockable On-Screen Display Controls
- Can Be Customized To Meet Your Needs
- 3 Year Warranty

The SRMTR-21.5R Sunlight Readable Touch Screen monitors are designed to operate in direct bright sunlight, or in other high ambient-light conditions. These state-of-the-art monitors produce over 1,000 nits of brightness (vs. 250-300 nits for standard monitors). This results in amazingly bright, crystal-clear HD images, even with direct, bright sunlight on the face of the screen. The SRMTR-21.5R Sunlight Readable Touch Screens are ideal for use in a wide range of industrial, law enforcement, aviation, marine, military, inspection, advertising and transportation applications where viewability in direct bright sunlight is crucial.

All **TRU-Vu** industrial LCD monitors are specifically designed for use in demanding applications. Every **TRU-Vu** monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of reliable worry-free operation. Visit [www.TRU-VuMonitors.com](http://www.TRU-VuMonitors.com) for more details.

Specifications	
LCD Panel	21.5" Color TFT LCD
Touch Technology	5-Wire Resistive
Touch Interface	USB
Display Resolution	1920 x 1080 (1080p/60 Full HD)
Display Area	18.76" x 10.55" (476.6 x 268.1 mm)
Pixel Pitch	0.248mm
Display Colors	16:7 M
Aspect Ratio	16:9
Brightness	1,000 nits
Contrast Ratio	1,000:1
Viewing Angle	170° (H) x 160° (V)
Response Time	5 ms Trf
Control	OSD (On-Screen Display) via Pushbuttons
Video Input Connectors	VGA, HDMI, DisplayPort
Video Inputs	VGA, HDMI, DisplayPort (DVI via supplied HDMI-to-DVI adapter)
Power Requirement	12 VDC / 90-240 VAC with included power brick
Power Consumption	45W
Enclosure	Powder-Coated Steel
Mounting	100 x 100 mm VESA
Operating Temperature	14° to 122° F / -10 to 50° C
Dimensions	19.51" (W) x 11.50" (H) x 0.72" (D) / 495.6 (W) x 292.2 (H) x 18.4 (D) mm
Weight	6.4 lbs. / 2.9 kg
Included Accessories	90-240 VAC Power Supply, VGA Cable, Remote Control, DVI Adapter