

SRMHXTRWP-10.4C

10.4" Sunlight Readable Waterproof Panel-Mount Touch Screen Monitors



- Produce Clear, Sharp Images Even in Direct Bright Sunlight
- 5-Wire Resistive Touch
- 1,500 Nits Brightness
- Stainless Steel Panel-Mount Enclosure
- NEMA 4X / IP65 Waterproof Front Face
- Automatic Ambient Light Sensor
- Auto Re-Start After Power Loss
- Lockable On-Screen Display Controls
- 3 Year Warranty

The SRMHXTRWP-10.4C Sunlight Readable Waterproof Panel-Mount Touch Screens are designed to operate in direct bright sunlight, or in other high ambient-light conditions. They utilize state-of-the-art LED backlights to produce over 1,500 nits of brightness (vs. 250-300 nits for standard monitors). The waterproof panel-mount enclosure enables installation in wash down or wet environments. The Ambient Light Sensor brightens or dims the screen as needed, depending upon ambient light conditions. The SRMHXTRWP-10.4C Sunlight Readable Waterproof Panel-Mount Touch Screens are ideal for use in a wide range of industrial, marine, military, manufacturing, inspection, advertising and transportation applications where viewability in direct bright sunlight is crucial.


All TRU-Vu industrial LCD monitors are specifically designed for use in demanding applications. Every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail/consumer-grade monitors. This ensures superior image quality, improved performance and greater durability. Our 3-Year Warranty ensures you of

	Specifications
MODEL	SRMHXTRWP-10.4C
LCD Panel	10.4" Color MVA LCD Panel (LED Backlights)
Touch Technology	5-Wire Resistive Touch
Touch Interface	USB
Resolution	1024 x 768 (XGA)
Viewable Area	8.31" (W) x 6.24" (H) (211.2 x 158.4 mm)
Pixel Pitch	0.2055 mm
Display Colors	16.2 M
Aspect Ratio	4:3
Brightness	1,500 nits
Contrast Ratio	3,000:1
Response Time	15 msec Trf
Viewing Angle	178° (H) x 178° (W)
Control	OSD (On-Screen Display) via Rear Panel Pushbuttons
Video Inputs	VGA and DVI
Power Requirement	12-24VDC
Power Consumption	13W (1.08A @ 12VDC)
Enclosure	Stainless Steel Panel-Mount (Rear Clamp)
Rating	NEMA 4X / IP65
Operating Temperature	-22° F to +176° F (-30° C to +80° C)
Humidity	8-90%RH
Shock	50 G (20 msec, ½ sine)
Vibration	1.5G RMS 10-200 HZ 30 mins/axis (X,Y,Z)
Dimensions	12.57" (W) x 9.87" (H) (319.20 x 250.70 mm)
Warranty	3 Years

SRMHXTRWP-10.4C

10.4" Sunlight Readable Waterproof Panel-Mount
Touch Screen Monitors

Dimensions: (mm)



Standard Accessories:

- VGA Cable
- Locking Power Pigtail

Available Options:

- DVI Input
- Private Label
- Other Customer - Specific Modifications



TRU-VU Monitors, Inc.

925 E Rand Road
Arlington Hts, IL
60004

Specifications subject to change without notice.

0517