

Full HD 1920x1080 in a Compact Form

Introducing three new block camera assemblies

AEG-6300-SDI (HDSDI)

&

AEG-6300-GE (GigE)

&

AEG-6300-HDMI (HDMI)*

**HDMI Model Coming Soon*

Incorporating Sony's latest FCB-EH6300 1080p block camera, our new complete camera assemblies offer a perfect solution for applications requiring a ruggedized housing with flexible configurations for indoor and outdoor environments.

Ideally suited for Surveillance, Low Vision, Broadcasting, Medical, Law Enforcement, EOD Tactical Robotic, POV, UAV, Machine Vision and many more.

Key Features Include:

- 1/2.8-type Exmor CMOS sensor
- 20X Optical Zoom (f=4.7mm (wide) to 94.0mm (tele))
- HDSDI or NTSC Output (Optional HDMI, HD Component and GigE also available)
- 1.7 Lux
- Day/Night Mode
- Auto White D mode
- E-Flip
- Mirror Image
- 1/4-20 Standard Mounting Bracket



Aegis
ELECTRONIC GROUP, INC
Phone 480-635-8400 * Fax 480-635-9272

OPTIONAL

ACCESSORIES:

- 12V DC Power Supply for HDSDI (ACY415A)
- 12V DC Power Supply for GigE (PD12P)
- Push Button Controller - (HDSDI only)
- BNC Cables (2m, 5m, 10m)
- RS232 Cables (2m, 5m, 10m, 15m)
- Video Cables
- HDSDI Cables
- Gigbit Ethernet Cables

For more information on any of our products or services please visit us on the Web at:

www.aegiselect.com

	HD	SD
Image sensor	1/3-type CMOS	
Number of total pixels	2M pixels	
Lens	20x optical zoom, F1.6 to F3.5 - f = 4.7mm to 94.0mm	
Digital zoom	12x (240x with optical zoom)	
Minimum working distance	10 mm (wide end) to 800 mm (tele end)	
S/N Ratio	More than 50 dB	
Electronic shutter	½ to 1/10,000s	
ICR	on / off / auto	
Minimum illumination	1.7 lx (typical) (F1.6, 50 IRE)	
Minimum illumination ICR	0.095 lx (typical) (F1.6, 50 IRE) HS-Mode	
White Balance	Auto, ATW, Indoor, Outdoor, One-push, Manual, Sodium Vapor Lamp Fix/Auto	
Gain control	Auto / Manual (-3 to 28 dB, 2dB 16 steps)	
Exposure control	Auto, Manual, Shutter Priority, Iris Priority, Bright, EV comp, Slow AE	
Focusing system	Full Auto (Normal AF/Interval AF/Zoom Trigger AF), One-push Trigger, Manual, Infinity	
Signal system	1080p/29.97 1080p/25	720p/59.94 720p/50 720p/29.97 720p/25
	1080i/59.94 1080i/50	
	One mode out of 12 modes can be selected	
Video output	HD-SDI (Options: Y/Pb/Pr, HDMI, GigE)	VBS:1.0 Vp-p (Sync Negative)
Sync system	Internal	
Camera control interface	RS232 signal level	
Storage temperature	-40 °C to 85 °C	
Operating temperature	-5 °C to 60 °C	
Power consumption	12.0 V DC / 5.0W	
Mass		
Dimensions (W x H x D)	HDSDI: 4.60" x 2.75" x 2.75" / GIGE: 6.25" x 3.00" x 3.00"	
Accessories (Included)	1/4-20 standard mounting bracket	

*All specification information is preliminary and subject to change without notice

Camera Pin Out

