



Mini Converter Sync Generator Technical Specifications

Description

Includes 6 crystal stabilized video reference outputs for referencing all the video equipment in your studio in either high definition Tri-Sync or standard definition Blackburst television standards. Perfect for small studios and outside broadcasts!

Connections

Analog Video

6 x common reference outputs.

Multi Rate Support

Via mini switches

Updates and Configuration

Via USB 2.0 high speed. (480 Mb/s)



Standards

Analog Format Support

625/25 PAL, 525/29.97 NTSC,
720p50, 720p59.94, 720p60,
1080PsF23.98, 1080PsF24, 1080i50,
1080i59.94, 1080i60, 1080p23.98,
1080p24, 1080p25, 1080p29.97,
1080p30.

Standards Analog Format Support
625/25 PAL, 525/29.97 NTSC,
720p50, 720p59.94, 720p60,
1080PsF23.98, 1080PsF24, 1080i50,
1080i59.94, 1080i60, 1080p23.98,
1080p24, 1080p25, 1080p29.97,
1080p30.

Software **Software Control**
Mac OS X™ and Windows™ software
upgrade via USB.

Internal Software Upgrade
Via included updater application.

Operating Systems



Mac OS X 10.9 Mavericks,
Mac OS X 10.10 Yosemite or later.



Windows 7 or Windows 8.

Settings Control Mini Switches or USB software.

Power Requirements **Power Supply**
+12V universal power supply
included with international socket
adapters for all countries. Cable tie
point.

Power Consumption
3.00 Watts

Operational Voltage Range
12V

Physical Specifications



Environmental Specifications **Operating temperature**
0° to 40° C (32° to 104° F)

Storage temperature
-20° to 45° C (-4° to 113° F)

Relative Humidity
0% to 90% non-condensing

What's Included Mini Converter Sync Generator
Software CD
12V universal power supply with international socket adapters

Warranty 3 Year Limited Manufacturer's Warranty.