

This information is brought to you by:



ELECTRONIC GROUP, INC
480-635-8400 p * aegis-g2@aegiselect.com
http://www.aegis-elec.com

DMD-4K

4K Ultra HD Video Decoder



4K DECODING

H.265
H.264

VIDEO COMPRESSION



COMPACT DESIGN



EASY-TO-USE CONTROLS

VIDEO DECODING

Interfaces	1x HDMI 1.3 output, supports SD/HD resolutions 1x HDMI 2.0 output, progressive only 1x Gigabit Ethernet
Supported Resolutions	Up to 2160p60 for H.265 & H.264
Video Codecs	H.264 (AVC) and H.265 (HEVC)
Protocols Supported	MPEG-2 TS, TSRTSP, RTSP, SRT, Zixi
Display Formats (HD)	50p, 59.94p and 60p @ 720p 50p, 59.94p and 60p @ 1080p 50i, 59.94i and 60i @ 1080i
Display Formats (UHD)	25p, 29.97p and 60p @ 2160p
Display Formats (ED)	50p @ 576p 60p @ 480p
Display View	Quad decode with 2x2 mosaic

AUDIO DECODING

Audio Codecs	MPEG-1 L1/L2 AAC-LC AAC-HE AAC-HEv2
--------------	--

SPECIFICATIONS

Dimensions	79 x 95 x 26 mm (3.1 x 3.7 x 1 in)
Weight	170 g (0.37 lb)
Power	12V DC with locking connector

OTHER

Additional Interfaces	1x USB 3.0 1x Micro-USB Console Port Available inside the enclosure: UART, I2C, SPI, GPIO
Software Control	HTTP-Based GUI: Configuration and Software Update

USE CASE



Z3Cam-4K



DMD-4K



2160p30

