

4/3" Distortionless Macro Lens

Model		VS-LLD50		
Focal Length(f)		50 mm		
Maximum Aperture Ratio		1: 2.0		
Optical Mag. Range		(∞) \times 0.05 \sim \times 0.3		
Optical Mag.		\times 0.05	\times 0.15	\times 0.3
FOV (V x H)	4/3"	272.0 \times 362.0 mm	90.7 \times 120.7 mm	45.3 \times 60.3 mm
	1"	225.2 \times 225.2 mm	75.1 \times 75.1 mm	37.5 \times 37.5 mm
	2/3"	142.0 \times 168.0 mm	47.3 \times 56.0 mm	23.7 \times 28.0 mm
WD		1012.4 mm	356.5 mm	205.4 mm
O/I (Object & Imager Distance)		1102.9 mm	447.0 mm	295.9 mm
Working F/# *Value at Iris Open		2.2	2.6	3.2
TV Distortion (4/3")		-0.01 %	-0.08 %	-0.09 %
Operation		Manual (Lock Screw M2)		
Wavelength		Visible		
Mount		C-Mount		
Flange Back		17.526 mm		
Sensor Size (max.)		4/3"		
Filter Thread		M 46 P= 0.75		
Weight (approx.)		250 g		
Dimension		ϕ 50.5 (max.) \times L = 73 mm		