



VZ-55SHB

55" SUPER NARROW BEZEL HIGH BRIGHTNESS LED VIDEO WALL MONITOR

0.44
MM

VZ-55SHB ADVANTAGES

- 55" 1080p CCTV LED Monitor
- Super Narrow **0.44 mm** Metal Bezel & **700 cd/m²** High Brightness
- Supports Max 4K (3840x2160)/60 Video Signal & Serial Control Software
- Supports HDMI (2.0) In/Out, DVI-D In, DP In, VGA In
- Supports HDCP 1.4 / 2.2
- Daisy Chain System - HDMI up to 15 x 15
- Auto Source & Power Recovery
- Mullion Compensation Applied
- Advanced Heat Management
- Digital / Analog Inputs
- 3D Comb-Filter & High Contrast
- Built to run 24/7/365
- 3-Year Warranty



MODEL #		VZ-55SHB
VIDEO		
Screen Size	55"	
Max. Resolution	1920 x 1080 @60Hz	
Pixel Pitch	0.630mm x 0.630mm	
Brightness	700cd/m ² (Typical)	
Contrast Ratio	1100:1	
Aspect Ratio	16 : 9	
Viewing Angle (H/V)	178° / 178°	
Display Color	1.06 B (10 Bit)	
Response Time	< 8ms	
INTERFACE		
VGA In (15Pin D-Sub)	1	
DP In	1	
DVI-D In	1	
HDMI 1 In	1	
HDMI 2 In / Out (Daisy Chain)	1 / 2	
USB In (Upgrade)	1	
RS-232 (RJ-45) In	1 (Serial Control / IR Receiver)	
RS-232 (RJ-45) Out	2 (Serial Control)	
Audio Out	1	
SPECIAL FEATURES		
Bezel Width	TOP and LEFT Side	0.017" / 0.44 mm
	BOTTOM and RIGHT Side	0.017" / 0.44 mm
	ACTIVE AREA to ACTIVE AREA	0.034" / 0.88 mm (Bezel to Bezel)
Advanced Anti-Image Residual Correlation	Support	
3D Comb-Filter	Support	
Language	English, Spanish, French and Portuguese	
SUPPORT RESOLUTION		
HDMI 1 (2.0) In	3840 x 2160 @ 60Hz	
HDMI 2 (2.0) In / Out	3840 x 2160 @ 60Hz	
DP In	3840 x 2160 @ 30Hz	
DVI-D In	3840 x 2160 @ 30Hz	
VGA In	1920 x 1080 @ 60Hz	

DIMENSIONS & WEIGHT	
Outline Dimension (W x H x D)	47.72" x 26.89" x 4.69" (1212.26 mm x 683.06 mm x 119.35 mm)
Net Weight / Gross Weight	65.91 lb (29.9 kg) / 88.18 lb (40.0 kg)
MOUNT	
Universal	600 x 400 (100 x4), M8 x L12 Screws
GENERAL	
Transmitter - IR Remote Control	YES
Power	Electrical Ratings Consumption
	AC100 ~ 240V (50/60Hz) 250 W (Max) / 0.5 W (Standby)
Regulations	FCC, RoHS
Warranty	Parts/ Labor
	3 Year / 3 Year
Operating Temperature	32 - 120°F / 0 - 50°C
Storage Temperature	32 - 140°F / 0 - 60°C
Operating Humidity (Non-Condensing)	20% ~ 80% RH
Compatible Mounts	Wall Ceiling Free Standing Mount
	VZ-XMS, VZ-WM71 VZ-CMKIT-04 VZ-FSM2x2, VZ-FSM3x2
Package Includes	Manual x 1, Power Cable x 1, HDMI Cable x 1, CAT5 Cable x 1, Converter (RJ45 to RS232) x 1, Remote Control x 1, IR Receiver x 1

