



2/3" 2.8/16mm C	2/3"	1/1.8"	1/2"
FOCAL LENGTH	f=16mm		
F-NUMBER	F=2.8-16		
PICTURE SIZE	6.6×8.8mm	5.4×7.2mm	4.8×6.4mm
ANGLE OF VIEW (∞)	VER. ANGLE	23.4°	19.2°
	HOR. ANGLE	30.9°	25.5°
	DIA. ANGLE	38.2°	31.6°
DISTORTION (TV)	-0.09%	-0.10%	-0.10%
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	88mm	72mm
	HOR.	117mm	96mm
	DIA.	147mm	120mm
MINIMUM FOCUS DISTANCE	0.2m		
FLANGE BACK	17.526mm in air		
BACK FOCUS	14.7mm in air		
FILTER SCREW SIZE	M30.5×0.5		
FRONT/REAR EFFECTIVE DIA.	FRONT $\phi$ 16.3mm		REAR $\phi$ 13.9mm
MOUNT	C-MOUNT		
EXIT PUPIL	-48.9mm		
TEMPERATURE RANGE	-10~+50 °C		
STORAGE TEMPERATURE RANGE	-20~+60 °C		
RESOLUTION CENTER/CORNER	CENTER 160lp/mm		CORNER 100lp/mm
WEIGHT	50g		

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。

		尺 度	1/1	工 場 番 号	S10-763
		機 種 名	2/3" f=16mm F2.8 5MP		
		機 種 番	LM16JC5MC-WP		
2022.04.27	作成年月日				