



1/1.8" 1.4/6mm C		1/1.8"	1/2"	1/3"
FOCAL LENGTH		f=6mm		
MAX. DIAMETER (RATIO)		F=1:1.4~16		
PICTURE SIZE		5.4x7.2mm	4.8x6.4mm	3.6x4.8mm
ANGLE	VER. ANGLE	48.4°	44.0°	33.7°
	HOR. ANGLE	62.7°	57.3°	44.0°
	DIA. ANGLE	75.2°	68.5°	53.4°
DISTORTION (TV)		-1.0%		
SHOOTING RANGE AT	VER.	188.7mm	166.9mm	123.9mm
	HOR.	255.8mm	225.8mm	166.9mm
MINIMUM FOCUS DISTANCE	DIA.	323.3mm	286.0mm	210.9mm
	MINIMUM FOCUS DISTANCE		0.2m	
FLANGE BACK		17.526mm in air		
BACK FOCUS		9.5mm in air		
FILTER SCREW-SIZE		M25.5x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 16.2mm		REAR ϕ 8.7mm
MOUNT		C-MOUNT		
EXIT PUPIL		-47.4mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 100lp/mm		CORNER 40lp/mm
WEIGHT		60 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	CG603NC
		機種名	1/1.8" F1.4 f=6mm		
2014.12.27	更新	機種番	LM6NCL 外観図		
2013.4.15	作成年月日				