



| 2/3" 2.8/8mm C | | 2/3" | 1/1.8" | 1/2" |
|---|-----------|---------------------------------|-------------|-------------|
| FOCAL LENGTH | | f=8mm | | |
| F-NUMBER | | F=2.8-16 | | |
| PICTURE SIZE | | 6.6 × 8.8mm | 5.4 × 7.2mm | 4.8 × 6.4mm |
| ANGLE OF VIEW (∞) | VER.ANGLE | 44.4° | 36.7° | 32.8° |
| | HOR.ANGLE | 57.6° | 48.1° | 43.1° |
| | DIA.ANGLE | 69.3° | 58.8° | 53.0° |
| DISTORSION (TV) | | -0.85% | -0.95% | -0.87% |
| FIELD OF VIEW (MINIMUM FOCUS DISTANCE) | VER. | 132mm | 107mm | 95mm |
| | HOR. | 178mm | 144mm | 127mm |
| | DIA. | 226mm | 183mm | 161mm |
| MINIMUM FOCUS DISTANCE | | 0.15m | | |
| FLANGE BACK | | 17.526mm in air | | |
| BACK FOCUS | | 10.8mm in air | | |
| FILTER SCREW SIZE | | M30.5×0.5 | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT φ 21.5mm REAR φ 11.9mm | | |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | -42.8mm | | |
| TEMPERATURE RANGE | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | CENTER 160lp/mm CORNER 100lp/mm | | |
| WEIGHT | | 55g | | |

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|-----------|------------------|---------------------|------------------|---------|
| | | 尺 度 | 1:1 | 工 場 番 号 | S10-632 |
| 2019/12/06 | フィルタサイズ追加 | 機 種 名 | 2/3" f=8mm F2.8 5MP | 機 種 番 号 | |
| 2019/09/26 | 誤記訂正 | | | | |
| 2019/02/08 | 作成 | 機 種 番 号 | | | |
| 日付 | 内容 | | | | |