



| | | | | | |
|---------------------------|------------|---|-----------------|----------------|--------|
| 2/3" | 1.4/25mm | C | 2/3" | 1/1.8" | 1/2" |
| FOCAL LENGTH | | | f=25mm | | |
| MAX. DIAMETER (RATIO) | | | F=1:1.4~16 | | |
| PICTURE SIZE | | | 6.6×8.8mm | | |
| ANGLE | VER. ANGLE | | 14.8° | 12.1° | 10.5° |
| | HOR. ANGLE | | 19.6° | 16.1° | 14.0° |
| | DIA. ANGLE | | 24.3° | 20.0° | 17.8° |
| DISTORTION (TV) | | | -0.04% | | |
| SHOOTING RANGE AT | VER. | | 53.3mm | 43.4mm | 38.6mm |
| | HOR. | | 71.1mm | 57.9mm | 51.4mm |
| MINIMUM FOCUS | DIA. | | 88.6mm | 72.4mm | 64.3mm |
| | DISTANCE | | | | |
| MINIMUM FOCUS DISTANCE | | | 0.2m | | |
| FLANGE BACK | | | 17.526mm in air | | |
| BACK FOCUS | | | 11.7mm in air | | |
| FILTER SCREW-SIZE | | | M27×0.5 | | |
| FRONT/REAR EFFECTIVE DIA. | | | FRONT φ24.0mm | REAR φ12.8mm | |
| MOUNT | | | C-MOUNT | | |
| EXIT PUPIL | | | -77.0mm | | |
| TEMPERATURE RANGE | | | -10~+50°C | | |
| STORAGE TEMPERATURE RANGE | | | -20~+60°C | | |
| RESOLUTION CENTER/CORNER | | | CENTER 100lp/mm | CORNER 80lp/mm | |
| WEIGHT | | | 90 g | | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|------------|-------|-----|------------------|------|---------|
| | | 尺度 | 1/1 | 工場番号 | HR940KW |
| | | 機種名 | 2/3" F1.4 f=25mm | | |
| 2013.11.21 | 更新 | 機種番 | LM25JC1MS 外観図 | | |
| 2013.4.15 | 作成年月日 | | | | |