



1" 1.8/25mm C	1"	2/3"	1/1.8"
FOCAL LENGTH	f=25mm		
F-NUMBER	F=1.8-16		
PICTURE SIZE	9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
ANGLE OF VIEW ( $\infty$ )	VER. ANGLE	22.0°	15.0°
	HOR. ANGLE	29.2°	20.2°
	DIA. ANGLE	36.4°	25.2°
DISTORTION (TV)	-0.97%	-0.48%	-0.32%
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	81mm	56mm
	HOR.	109mm	74mm
	DIA.	138mm	93mm
MINIMUM FOCUS DISTANCE	0.2m		
FLANGE BACK	17.526mm in air		
BACK FOCUS	24.5mm in air		
FILTER SCREW SIZE	M27x0.5		
FRONT/REAR EFFECTIVE DIA.	FRONT $\phi 18.9$ mm		REAR $\phi 18.7$ mm
MOUNT	C-MOUNT		
EXIT PUPIL	-225.3 mm		
TEMPERATURE RANGE	-10~+50 °C		
STORAGE TEMPERATURE RANGE	-20~+60 °C		
RESOLUTION CENTER/CORNER	CENTER 160lp/mm		CORNER 100lp/mm
WEIGHT	160g		

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。

		尺 度	1/1	工 場 番 号	LM25HC-VS
		機 種 名	1" f=25mm F1.8 VIS-SWIR		
		機 種 番	LM25HC-VIS-SW		
2020.09.15	作成年月日				S10-705