



| 2/3" 1.4/25mm C           |            | 2/3"                                     | 1/1.8"  | 1/2"           |
|---------------------------|------------|--|---------|----------------|
| FOCAL LENGTH              |            | f=25mm                                   |         |                |
| MAX. DIAMETER (RATIO)     |            | F=1:1.4,4,8,16                           |         |                |
| ELEMENT                   |            | 6群 8枚                                    |         |                |
| PICTURE SIZE              |            | 6.6×8.8mm                                | 5.4×7.2 | 4.8×6.4        |
| ANGLE                     | VER. ANGLE | 14.8°                                    | 12.1°   | 10.5°          |
|                           | HOR. ANGLE | 19.6°                                    | 16.1°   | 14.0°          |
|                           | DIA. ANGLE | 24.3°                                    | 20.0°   | 17.5°          |
| DISTORTION (TV)           |            | -0.04%                                   |         |                |
| SHOOTING RANGE AT         | VER.       | 53.3 mm                                  | 43.4    | 38.6           |
| MINIMUM FOCUS             | HOR.       | 71.1 mm                                  | 57.9    | 51.7           |
| DISTANCE                  | DIA.       | 89.0 mm                                  | 72.4    | 64.6           |
| MINIMUM FOCUS DISTANCE    |            | 0.2m                                     |         |                |
| FLANGE BACK               |            | 17.526 mm in air                         |         |                |
| BACK FOCUS                |            | 11.7mm in air (Mechanical 10.2mm in air) |         |                |
| FILTER SCREW SIZE         |            | M27×0.5                                  |         |                |
| FRONT/REAR EFFECTIVE DIA. |            | FRONT φ24.0mm                            |         | REAR φ12.8mm   |
| MOUNT                     |            | C-MOUNT                                  |         |                |
| EXIT PUPIL                |            | -77.0mm                                  |         |                |
| TEMPERATURE RANGE         |            | -10~+50°C                                |         |                |
| STORAGE TEMPERATURE RANGE |            | -20~+60°C                                |         |                |
| RESOLUTION CENTER/CORNER  |            | CENTER 100lp/mm                          |         | CORNER 80lp/mm |
| WEIGHT                    |            | 83g                                      |         |                |

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。

|            |       |     |                  |      |         |
|------------|-------|-----|------------------|------|---------|
|            |       | 尺度  | 1/1              | 工場番号 | HR940WP |
|            |       | 機種名 | 2/3" F1.4 f=25mm |      |         |
|            |       | 機種番 | LM25JCM-WP 外觀図   |      |         |
| 2018.05.31 | 作成年月日 |     |                  |      |         |