



| | | | | | |
|---|-----------------|------------|-----------------|-------|-----------|
| | 1.1" | 1.8/16mm C | 1.1" | 1" | 2/3" |
| FOCAL LENGTH | f=16mm | | | | |
| F-NUMBER | F=1.8-16 | | | | |
| PICTURE SIZE | 10.6×14.1mm | | 9.6×12.8mm | | 6.6×8.8mm |
| ANGLE OF VIEW (∞) | VER. ANGLE | 36.7° | 33.4° | 23.3° | |
| | HOR. ANGLE | 48.0° | 43.6° | 30.8° | |
| | DIA. ANGLE | 58.3° | 53.1° | 37.9° | |
| DISTORTION (TV) | -0.4% | | | | |
| FIELD OF VIEW (MINIMUM FOCUS DISTANCE) | VER. | 77mm | 70mm | 48mm | |
| | HOR. | 102mm | 93mm | 64mm | |
| | DIA. | 127mm | 116mm | 80mm | |
| MINIMUM FOCUS DISTANCE | 0.1m | | | | |
| FLANGE BACK | 17.526mm in air | | | | |
| BACK FOCUS | 11.9mm in air | | | | |
| FILTER SCREW-SIZE | M35.5×0.5 | | | | |
| FRONT/REAR EFFECTIVE DIA. | FRONT φ26.5mm | | REAR φ17.0mm | | |
| MOUNT | C-MOUNT | | | | |
| EXIT PUPIL | -58.9mm | | | | |
| TEMPERATURE RANGE | -10~+50°C | | | | |
| STORAGE TEMPERATURE RANGE | -20~+60°C | | | | |
| RESOLUTION CENTER/CORNER | CENTER 200lp/mm | | CORNER 100lp/mm | | |
| WEIGHT | 200g | | | | |

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

| | | | | |
|------------|-------|-----|------------------|------|
| | | 尺度 | 1/1 | 工場番号 |
| | | 機種名 | 1.1" F1.8 f=16mm | |
| | | 機種番 | LM16FC24M 外観図 | |
| 2017.09.15 | 作成年月日 | | | |