



2/3" 1.4/16mm C		2/3"	1/1.8"	1/2"
FOCAL LENGTH		f=16mm		
MAX. DIAMETER (RATIO)		F=1:1.4~16		
ELEMENT		9 GROUPS 10 ELEMENTS		
PICTURE SIZE		6.6x8.8mm	5.4x7.2mm	4.8x6.4mm
ANGLE	VER. ANGLE	22.7°	18.6°	16.6°
	HOR. ANGLE	29.9°	24.7°	22.0°
	DIA. ANGLE	36.9°	30.6°	27.3°
DISTORTION (TV)		0.03%		
SHOOTING RANGE AT	VER.	48.4mm	39.6mm	35.2mm
MINIMUM FOCUS	HOR.	64.6mm	52.9mm	47.0mm
DISTANCE	DIA.	81.1mm	66.3mm	58.8mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		11.6mm in air		
FILTER SCREW-SIZE		M30.5x0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 24.5mm		REAR ϕ 16.6mm
MOUNT		C-MOUNT		
EXIT PUPIL		-105.7mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION	CENTER/CORNER	CENTER 160本/mm		CORNER 100本/mm
WEIGHT		125 g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

		尺度	1/1	工場番 加番号	CH1053
		機種名	2/3" F1.4 f=16mm		
2014.12.25	更新	機種番	LM16JC5M2 外觀図		
2013.4.15	作成年月日				