



ximea



xiQ
USB3 compact cameras



xiQ compact USB3 cameras

A superb workhorse: smallest, lightest and single board design

Facts

- Small 26 x 26 mm or 1x1" front face size
- Lightweight at 32 g
- VGA sensor at > 500 fps
- 1080p Full HD at 170 fps
- RGB, monochrome and NIR enhanced sensors

Features

- Standardized industrial grade USB interface
- Unique single PCB layout
- Lowest power consumption
- Flexible/programmable GPIO option
- USB3 Vision[®] compliant
- Very compact cameras
- Available as housed, semi-housed and board level versions
- Rugged and lightweight, aluminum alloy CNC machined housing



Big in performance, small in size


Designed to be tiny in size, low in mass and with high efficiency, this series is a tremendous asset in the machine vision and mobile scenarios. Its compact design offers superb options in mobile solutions. The extremely low power consumption results in excellent properties in heat sensitive environments.

Versatile


The semi-housed version comes as a complete camera with a cutout in the housing for flex ribbon connection. It relieves the integrator of the necessity to handle sensitive board level units where sensors and electronics are easily damaged in an integration process. The flat ribbon cable saves valuable z-axis space in cramped environments. Data, power, and IOs all run through this cable making integration a breeze.

Housing examples

Standard C/CS-mount with model-specific, customized filter glass





Housed cameras with Micro-B connector



- 1 * fast opto-isolated input
- 1 * fast opto-isolated output
- LED indicators
- SuperSpeed USB3.0 image data port

Semi housed cameras with 'FL' ribbon cable connector



Supported operating systems



Windows



Linux

macOS

Language support



Standards

GEN<i>i>CAM
TRANSPORT LAYER

USB[®]
VISION

Supported vision libraries



MATLAB



HALCON
a product of MVTec



and many more ...

Sensors and models

Model		Sensor	Resolution	Pix. size [µm]	ADC [bits]	DR [dB]	Sensor size / diagonal [mm]	Optical size	Fps	Power typical [W]
MQ003MG-CM ^{4,8}	b/w	CMOSIS CMV300	648 x 480 0.3 Mpix	7.4	12	60 ³	4.8 x 3.6 6	1/3"	500 ¹	1.5
MQ003CG-CM ^{4,8}	color	CMOSIS CMV300	648 x 480 0.3 Mpix	7.4	12	60 ³	4.8 x 3.6 6	1/3"	500 ¹	1.5
MQ013MG-E2 ^{4,5,7,8}	b/w	e2v EV76C560	1280 x 1024 1.3 Mpix	5.3	10	60	6.8 x 5.4 8.6	1/1.8"	61 ¹	0.75
MQ013CG-E2 ^{4,7,8}	color	e2v EV76C560	1280 x 1024 1.3 Mpix	5.3	10	60	6.8 x 5.4 8.6	1/1.8"	61 ¹	0.75
MQ013RG-E2 ^{4,5,7,8}	b/w NIR	e2v EV76C661	1280 x 1024 1.3 Mpix	5.3	10	60	6.8 x 5.4 8.6	1/1.8"	61 ¹	0.75
MQ013MG-ON ^{4,8}	b/w	OnSemi PYTHON1300	1280 x 1024 1.3 Mpix	4.8	10	56	6.1 x 4.9 7.8	1/2"	172/210 ²	1.3
MQ013CG-ON ^{4,8}	color	OnSemi PYTHON1300	1280 x 1024 1.3 Mpix	4.8	10	56	6.1 x 4.9 7.8	1/2"	172/210 ²	1.3
MQ013RG-ON ^{4,8}	b/w NIR	OnSemi PYTHON1300	1280 x 1024 1.3 Mpix	4.8	10	56	6.1 x 4.9 7.8	1/2"	172/210 ²	1.3
MQ022MG-CM ^{4,5,7}	b/w	CMOSIS CMV2000	2048 x 1088 2.2 Mpix	5.5	10	60 ³	11.3 x 6.0 12.7	2/3"	170 ¹	1.5
MQ022CG-CM ^{4,5,7}	color	CMOSIS CMV2000	2048 x 1088 2.2 Mpix	5.5	10	60 ³	11.3 x 6.0 12.7	2/3"	170 ¹	1.5
MQ022RG-CM ^{4,5,7}	b/w NIR	CMOSIS CMV2000	2048 x 1088 2.2 Mpix	5.5	10	60 ³	11.3 x 6.0 12.7	2/3"	170 ¹	1.5
MQ042MG-CM ^{4,5,7}	b/w	CMOSIS CMV4000	2048 x 2048 4.1 Mpix	5.5	10	60 ³	11.3 x 11.3 15.9	1"	90 ¹	1.5
MQ042CG-CM ^{4,5,7}	color	CMOSIS CMV4000	2048 x 2048 4.1 Mpix	5.5	10	60 ³	11.3 x 11.3 15.9	1"	90 ¹	1.5
MQ042RG-CM ^{4,5,7}	b/w NIR	CMOSIS CMV4000	2048 x 2048 4.1 Mpix	5.5	10	60 ³	11.3 x 11.3 15.9	1"	90 ¹	1.5
MQ042MG-CM-TG ^{4,7}	b/w	CMOSIS CMV4000	2048 x 2048 4.1 Mpix	5.5	10	60 ³	11.3 x 11.3 15.9	1"	90 ¹	1.5
MQ042CG-CM-TG ^{4,7}	color	CMOSIS CMV4000	2048 x 2048 4.1 Mpix	5.5	10	60 ³	11.3 x 11.3 15.9	1"	90 ¹	1.5

Notes

- ¹ Full resolution, RAW8 format
- ² Full resolution, RAW8 format, sensor is not operating in Zero ROT mode / sensor is operating in Zero ROT mode
- ³ HDR mode available
- ⁴ In the model name please add -BRD to address the board-level camera
- ⁵ In the model name please add -FL-BRD to address the board-level camera with horizontal orientation of flat ribbon connector
- ⁶ In the model name please add -FL to address camera with horizontal orientation of flat ribbon connector
- ⁷ In the model name please add -SL-BRD to address slim-line board-level camera
- ⁸ The recent sales figures have declined to a level which can no longer be sustained, resulting in a discontinuation of the camera. To find alternatives or if you have further questions, please contact our sales team.

Further information

Please visit us at www.ximea.com for complete and up-to-date specifications. Get in touch with our teams at sales@ximea.com. We will be glad to assist!



Sales offices

Worldwide

XIMEA GmbH

Am Mittelhafen 16
48155 Münster
Germany

Tel: +49 (251) 202 408 0

Slovakia and Czech Republic

XIMEA s.r.o

Lesna 52
900 33 Marianka
Slovakia

Tel: +421 (2) 205 104 26

America

XIMEA Corp.

8725 W 14th Ave
80215 Lakewood, CO
USA

Tel: +1 (303) 389 983 8

info@ximea.com

