



1.2"	2.4/25mm C	1.2"	1.1"	1"
FOCAL LENGTH		f=25mm		
F-NUMBER		F=1, 2.4, 2.8, 4, 5, 6, 8		
PICTURE SIZE		11.5×15.4mm	10.6×14.1mm	9.6×12.8mm
ANGLE OF VIEW (∞)	VER. ANGLE	26.1°	24.1°	21.9°
	HOR. ANGLE	34.9°	32.0°	29.1°
	DIA. ANGLE	43.2°	39.7°	36.2°
DISTORTION (TV)		-1.0%		
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	233mm	214mm	194mm
	HOR.	315mm	287mm	260mm
	DIA.	397mm	362mm	328mm
MINIMUM FOCUS DISTANCE		0.5m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		15.6mm in air		
FILTER SCREW-SIZE		M34.0×0.5		
FRONT/REAR EFFECTIVE DIA.		FRONT φ21.5mm		REAR φ15.6mm
MOUNT		C-MOUNT		
EXIT PUPIL		-46.2mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 200lp/mm		CORNER 125lp/mm
WEIGHT		90g		

NOTE: Specifications and availability are subject to change without notice  
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	LM25EC-IR
		機種名	1.2" F2.4 f=25mm		
2024.08.28	寸法修正	機種番	LM25EC-IR	外觀図	
2024.08.01	作成年月日				