

VL-ZBTP-19H

19" Touch Screen Monitor

- 19" Industrial-Grade Touch Screen
- Projected Capacitive Touch (USB)
- HID Compliant; No Additional Drivers Required
- Edge-to-Edge All-Glass Front Surface
- Resolution: 1280 x 1024 (SXGA)
- VGA & HDMI Video Inputs
- Can Be Customized to Meet Your Needs



19" TOUCHSCREEN MONITOR

The VL-ZBTP-19H 19" touchscreen monitors utilizes a Projected Capacitive touch screen which allows for up-to 10 points of Multi-Touch functionality.

Our image quality is exceptionally clear and bright. The contact activation point is extremely accurate. All models in this series feature a USB touch interface. They offer 1280 x 1024 resolution and a 4:3 aspect ratio. Additionally, the panels have 380 nits brightness.

RUGGED INDUSTRIAL TOUCHSCREEN

This series receives our exclusive TRU-Tuff treatment. Moreover, the TRU-Tuff process includes RTV silicone on all connections and critical components. Additionally, all wires are dressed, tie-wrapped and secured. Lastly, we apply ThreadLock to all screws to ensure they remain secured. Most importantly, this results in a rugged, dependable monitor you can rely on. They can operate on 12 VDC or 100-240 VAC with Included Power Brick.

TOUCH SCREENS FOR DEMANDING APPLICATIONS

The VL-ZBTP-19H also provide a brighter-than-normal, with 380 nits brightness. The result is crisp, vibrant video images. TRU-Vu industrial LCD monitors are specifically designed for use in demanding industrial, commercial, and A/V applications. For instance, every TRU-Vu monitor utilizes industrial-grade components and high-end LCD panels not found in retail or consumer-grade monitors. This ensures superior image quality, improved performance and greater durability.

The VL-ZBTP-19H industrial 19" LCD touch screens offer a variety of video inputs and are available in standard, open frame, rack mount, panel mount, NEMA/IP waterproof, and touch screen configurations. An extensive list of available OEM options enables you to customize a solution to your specific needs. They can also be private-labeled with your company name and/or logo on the front bezel.

TRU-VU TOUCH SCREENS DEPLOYED WORLDWIDE

The VL-ZBTP-19H 19" touchscreen monitors with 4:3 aspect ratio are deployed in many industries and applications. This includes manufacturing plants, machine vision inspection systems, and food and beverage plants. They are also found in surveillance systems, specialty vehicles and museums.

We offer numerous other monitors in similar sizes and brightness levels from which to choose.

OUR TECHNICAL EXPERTS ARE READY TO HELP YOU FIND THE BEST 19" INDUSTRIAL DISPLAY

With over 200 LCD monitors and touch screens on our site, selecting the ideal equipment, or touch screen solution may be a bit overwhelming. To help narrow down the choices, check out our [Advanced Search Tool](#). For example, this enables you to filter by your own specific search requirements. See all monitors that can operate on 24VDC.

Finally, our team members are ready to help! We can determine the exact solution that will meet your specific needs. Certainly, TRU-Vu will help provide clear images for your operating requirements. Call **(847) 259-2344** today to speak with one of our specialists. Above all, we will listen. It's one of the things we do best. Our professional advisors will ensure the monitor or touch screen you receive will be and do everything you had hoped it would!

If you prefer, fill out a [quick form](#) with your requirements, and we will guide you to the proper models that will work best.


To see technical information, tips, tricks and guides to LCD monitors and technology, visit our [TECH CENTER](#).

SPECIFICATIONS

VL-ZBTP-19H	
LCD Panel	19" Color LCD; LED Backlights
Touch Screen Type	Projected Capacitive
Touch Interface	USB
Resolution	1280 x 1024 (SXGA)
Viewing Area	14.81" (W) x 11.85" (H) (376.3 mm x 301 mm)
Pixel Pitch	0.294mm
Display Colors	16.7 M
Aspect Ratio	4:3 (5:4)
Brightness	380 nits
Contrast Ratio	1,000:1
Viewing Angle	170° (H) x 160° (V)
Response Time	10 msec (Trf)
Video Input	VGA & HDMI
Power Requirement	12VDC / 100-240VAC via Included AC Adapter
Enclosure	Zero-Bezel/Painted Steel
Mounting	Rear VESA 75x75mm & 100 x 100mm Mounting Holes (optional L-Brackets available for flush-mounting)
Operating Temperature	32° to 122°F (0° to +50°C)
Dimensions	16.89" W x 14.02" W x 1.76" D (429mm W x 356mm H x 45.6mm D)
Approvals	CCC, ETL, FCC, CE, CB, RoHS

Note: Specifications subject to change without notice.

DIMENSIONS (MM)



Standard Accessories:

- 90-240 VAC Power Brick
- VGA Cable
- USB Cable

Available Options:

- Optical Bonding
- Private-Label
- Wall-Mount Bracket
- Other Customer - Specific Modifications